

# CECI 160

## IN-GROUND



DRIVE-OVER in-ground luminaries with no visible screws, made of shockproof resin material, UV-rays stabilized, rust and corrosion-free. Round or square shape available with several cover versions. Supplied as standard with TÜV approved, long-life and efficient **GX53 LED lamp included**. Insulation class II, Protection rating IP67.



CECI 160  
3F1.000



CECI 160-2L  
3F2.000



CECI 160-3L  
3F3.000



CECI 160-SQ  
3F4.000

*Apparecchio per incasso a terra CARRABILE e senza viti a vista, realizzato in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Disponibile con forma quadrata o circolare in diverse versioni di cover. Fornito con inclusa lampadina a LED GX53 approvata TÜV, di lunga durata ed elevata efficienza. Classe di isolamento II, grado di protezione IP67.*



3F3.000.D1L






**CECI 160 - COMPONENTS**



**IP67**




**COVER** with no visible screws made of shockproof resin material, UV-rays stabilized, rust and corrosion free. Round or square design, 2 or 3 light versions available for a diffuse or directed light emission.



**COVER** senza viti a vista realizzata in resina antiurto, stabilizzata ai raggi UV, inattaccabile da ruggine e corrosione. Disponibile nelle versioni quadrata o ad anello, a 2 aperture e a 3 aperture per permettere un'emissione della luce diffusa o direzionata.

**DIFFUSER** made of high impact and high-pressure load resistant resin material (PC), complete with silicone rubber gasket to ensure high protection against external agents. Frosted or coloured versions, to get a customized ambience.

**DIFFUSORE** in resina antiurto altamente resistente al carico (PC), completo di guarnizione in gomma siliconica per garantire un alto livello di protezione contro gli agenti esterni. Disponibile nella versione satinata o colorata, per ottenere un'ambientazione personalizzata.



**HOUSING** made of shockproof resin material, provided with double holes and double watertight cable glands for safe connecting cable.

**CASSA** realizzata in resina antiurto, provvista di doppi fori e doppio pressacavo a tenuta stagna, per consentire in maniera sicura l'ingresso e l'uscita delle connessioni elettriche.

**INSTALLATION HOUSING** made of shockproof resin material to be fixed into the ground before installing the luminaries.

**CONTRO-CASSA** in resina antiurto da fissare al suolo prima dell'installazione degli apparecchi.

**CECI 160**



**Dimensions and weight**  
Installation housing depth: 111 mm  
Diameter: Ø 160 mm  
Weight: 0,8 Kg

**Cover colours:**



**Diffuser PC:**



**GX53 LED**

\*ADD SUFFIX



	7 W	800 Lm	4000 K	.C1L
			3000 K	.C1R
	10 W	1200 Lm	4000 K	.D1L
			3000 K	.D1R

In-ground supplied as standard with TÜV approved, long-life and efficient **GX53 LED lamp** included. Different wattages available. Quick and easy lamp replacement for a very simple maintenance after installation.

- **COST SAVING:** long-life and efficient LED light sources
- **BUILT-IN DRIVER:** quick and easy lamp replacement
- **GREAT FLEXIBILITY:** GX53 standard lamp holder
- **FUTURE-PROOFED LUMINARIES:** performances easy to upgrade to latest technology developments
- **SUITABLE FOR OUTDOOR USE:** built-in driver fully protected against heat and humidity by silicone paste.

**7W 800 Lm = 75W incandescent**  
**SAVE 90%**



**10W 1200 Lm = 100W incandescent**  
**SAVE 90%**



**LED LAMPS**



More technical details about TÜV approved Fumagalli LED Lamps on page 512.

\*ADD THESE SUFFIXES TO THE REFERENCES MENTIONED IN THE CATALOGUE

**CECI 160**  
IN-GROUND



3F2.000.AUD1L



3F1.000.C1L




3F4.000.C1L



3F3.000.C1L





CECI 160		
3F1.000.C1L	<b>7W</b>	3F1.000.C1R
3F1.000.D1L	<b>10W</b>	3F1.000.D1R
4000K	GX53 LED LAMP INCLUDED	3000K

Pcs 18  
Kg 14,3  
mc 0,084

CECI 160-3L		
3F3.000.C1L	<b>7W</b>	3F3.000.C1R
3F3.000.D1L	<b>10W</b>	3F3.000.D1R
4000K	GX53 LED LAMP INCLUDED	3000K

Pcs 18  
Kg 14,3  
mc 0,084

CECI 160-2L		
3F2.000.C1L	<b>7W</b>	3F2.000.C1R
3F2.000.D1L	<b>10W</b>	3F2.000.D1R
4000K	GX53 LED LAMP INCLUDED	3000K

Pcs 18  
Kg 14,3  
mc 0,084

CECI 160-SQ		
3F4.000.C1L	<b>7W</b>	3F4.000.C1R
3F4.000.D1L	<b>10W</b>	3F4.000.D1R
4000K	GX53 LED LAMP INCLUDED	3000K

Pcs 18  
Kg 14,3  
mc 0,084